

PART **G** Additional information

This part provides reference information, including a glossary of terms.

Contents

Glossary	G-3
Tait Electronics Limited Software Licence Agreement	G-7

Glossary

active

The 'on' (asserted) state of a signal or indicator.

ADC

Analog to digital converter. An electronic device that outputs binary data dependant upon the magnitude of voltage input.

brownout

A dip in the supply voltage sufficient to put the control section into hardware reset.

calibration

The process of determining the **calibration data** for a radio. Calibration is normally only carried out during product manufacture or major service.

calibration data

The set of coefficients for each of the electronic tuning variables, as a function of frequency, which allows the radio to calculate the **configuration data** for any frequency it operates on. The **calibration data** is unique for each radio.

call

A complete exchange of information between two or more parties. In **trunked mode**, this may occur on the **control channel** or on a **traffic channel**.

CCTM

Computer controlled test mode. The operating mode of the radio whereby computer equipment can control various radio functions by sending commands down a serial link to the radio.

channel

A receive/transmit frequency pair.

configuration

The determination and setup of the **configuration data** for a given frequency from the programmed **calibration data** (i.e. electronic tuning).

configuration data

The data set corresponding to the value of the electronic tuning variables on a given channel. This is calculated for each frequency from the **calibration data**.

control channel

The **channel** used by a **trunking system** to control the radio.

conventional mode

The mode of operation whereby the radio behaves as a conventional two-way radio (i.e. non-trunked operation).

CTCSS

Continuous Tone Controlled Squelch System. Continuous, subaudible coding on the channel for the purpose of segregating user groups.

DAC

Digital to analog converter. An electronic device that outputs a voltage dependent upon the value of binary data input.

database

The set of programmable data points that allows the product to be customised for a particular application or mode of operation.

Note: Terms that appear in **bold sans serif** font are also defined in this glossary.

DC

Direct current.

DCS

Digitally coded squelch. Continuous, subaudible coding (repeating digital code sequence) on the **channel** for the purpose of segregating user groups.

delayed

Key action. The input is not actioned until it has been stable for the duration of the debounce interval.

dialled string

A sequence of characters entered via the keypad. May contain **numbers, labels, ‘*’** or **‘#’**. Used to initiate **calls** or invoke special functions.

dialling

The act of entering a number or label by typing in successive characters on the keyboard.

DSP

Digital signal processor.

DTMF

Dual tone multiple frequency. Method of encoding digits (0 to 9) and characters (A to F), each as a pair of eight standard tones.

economy mode

When the radio is cycling between the **receive mode** and **standby** state. Available on Tait Orca conventional handportables.

ECR

External call request.

EPROM

Erasable programmable read only memory.

EPTT

External press-to-talk.

ESN

The MPT1343 defined electronic serial number of the radio.

FFSK

Fast frequency shift keying. The signalling method employed in trunked radios. Data is represented by 1 cycle of 1200 Hz (logic 1) or 1.5 cycles of 1800 Hz (logic 0) and is transmitted at 1200 baud.

fixed (indicators)

Do not time out of their own accord. Generally indicate mode of operation or state.

idle

The state of the radio in **trunked mode** when it is not engaged in a call or call setup, or in **conventional mode** when the radio is not transmitting.

IF

Intermediate frequency.

inactive (indicator)

The ‘off’ (unasserted) state of a signal or indicator.

label

A plain language word (1 to 8 characters long) that is defined to represent a valid dialled string at radio programming time.

LCD

Liquid crystal display.

LED

Light emitting diode.

LPF

Low pass filter.

MCU

Micro control unit.

mute

The receive audio gating element. When active, receive audio is passed to the speaker. The decision to activate/deactivate the audio signal path is based on an evaluation of signaling codes (**CTCSS**, **DCS**, **Selcall**) contained in the audio information (contrast with **squelch**).

number

A simple **string** that corresponds to an MPT1343 defined called party identifier.

PA

Power amplifier.

PABX

Private automatic branch exchange.

PCB

Printed circuit board.

PLL

Phase locked loop.

PLCC

Plastic leaded chip carrier.

PMR

Private mobile radio.

programming mode

The mode of operation of the radio in which computer equipment can read from and write to the radio **database**.

PSTN

Public switched telephone network.

RAM

Random access memory.

receive mode

This is the state wherein the radio is producing a valid busy output, irrespective of whether any audio output is produced at the speaker

terminals. The +5V-ECON supply is on, and sufficient time has elapsed for various circuit blocks to settle.

RF

Radio frequency.

RSN

The radio's unique serial number.

RSSI

Received signal strength indicator.

SCI

Serial communications interface. This is the serial interface from the radio to an external device, normally utilising transmit and receive data, signal and ground lines.

Selcall

Selective calling. Sequential tone burst coding on the channel for the purpose of selecting an individual or group with which to communicate.

selecting

The act of picking a **label** from a displayed list using the arrow keys.

signalling

Non-voice coding on the channel for the purpose of identifying parties and/or segregating user groups, e.g. **CTCSS**, **DCS**, **Selcall**.

SMD

Surface mount device.

SOIC

Small outline integrated circuit.

SOT

Small outline transistor.

squelch

The channel busy detection circuitry. The decision to activate/deactivate the audio signal path is based on a signal-to-noise measurement on the received **RF** signal (the squelch circuitry precedes the **mute** circuitry).

standby state

This is essentially when the +5V-ECON line is off. That is, when the radio is drawing the minimum current, while still being switched on.

string (simple)

A sequence of the characters 0 to 9, *, #, which instructs the radio to initiate a call or perform some other function.

successful (call)

A **call** for which a **traffic channel** is assigned.

system restart

The action taken by the radio (e.g. in response to the '^' character received on the **SCI**) where it immediately ceases current operation, then behaves as though it has just been switched on.

TCXO

Temperature compensated crystal oscillator (voltage controlled). The frequency reference for the **RF** part of the radio.

test mode

The operating mode of the radio whereby computer (computer equipment can control various radio functions by sending controlled) commands down a serial link to the radio.

traffic channel

The channel used by the radio for the duration of a **call**.

transmit mode

The radio has validated a request and commenced or completed the sequence of switching out of **receive mode**. This does not necessarily imply that **RF** is being generated.

trunked mode

The mode of operation of the radio whereby the radio obeys commands on the **control channel** and generally operates as proscribed in MPT1343.

trunking system

The infrastructure comprising repeaters and radios required to support a number of **control channels** and **traffic channels**.

VCO

Voltage controlled oscillator. The oscillator that generates either the on-channel signal to drive the transmitter, or the local oscillator to mix incoming **RF** signals to the **IF** of the radio. The instantaneous frequency of the VCO is determined by a combination of the synthesiser (**PLL**) and the modulation signals TCXO-MOD and VCO-MOD.

VOX

Voice operated transmit.

Tait Electronics Limited

Software Licence Agreement

This legal document is an Agreement between you (the "Licencee") and Tait Electronics Limited ("Tait"). By opening this product package and/or using the product you agree to be bound by the terms of this Agreement. If you do not agree to the terms of this Agreement, do not open the product package and immediately return the unopened product package to Tait. If you open the product package, that will be deemed to be acceptance of the terms of this licence agreement.

Licence

In consideration of the payment of the Licence Fee, which forms part of the price you paid for products you acquired from Tait or its subsidiary or agent (the "products") and our willingness to be bound by the terms of this agreement, Tait grants to you as Licencee the non-exclusive right to use the copy of a Tait software program included in the products (the "Software").

In particular, the Licencee may use the program on a single machine and if the software is supplied on a diskette, the licensee may:

- (a) Copy the program into any machine readable or printed form for backup purposes in support of your use of the program on the single machine (certain programs, however, may include mechanisms to limit or inhibit copying; they are marked "copy protected"), provided the copyright notice must be reproduced and included on any such copy of the Software.
- (b) Merge it into another program for your use on the single machine. (Any portion of this program merged into another program will continue to be subject to the terms and conditions of this Agreement.)

The Licencee may not duplicate, modify, reverse compile or reverse assemble the Software in whole or part.

Title to software

This agreement does not constitute a contract of sale in relation to the Software supplied to the Licencee. Notwithstanding the Licencee may own the magnetic or other physical media on which the Software was originally supplied, or has subsequently been recorded or fixed, it is a fundamental term of this Agreement that at all times title and ownership of the Software, whether on the original media or otherwise, shall remain vested in Tait or third parties who have granted licences to Tait.

Term and termination

This Licence shall be effective until terminated in accordance with the provisions of this Agreement. The Licencee may terminate this Licence at any time by destroying all copies of the Software and associated written materials. This Licence will be terminated automatically and without notice from Tait in the event that the Licencee fails to comply with any term or condition of this Agreement. The Licencee agrees to destroy all copies of the Software and associated written materials in the event of such termination.

Limited warranty

The Software is supplied by Tait and accepted by the Licencee "as is" without warranty of any kind either expressed or implied, including but not being limited to any implied warranties as to merchantability or fitness for any particular purpose. The entire risk as to the quality and performance of the Software vests in the Licencee. Should the Software prove to be defective, the Licencee (and not Licensor or any subsidiary or agent of the Licensor) shall assume the entire cost of all necessary servicing, repair or correction. Tait does not warrant that the functions contained in the Software will meet the Licencee's requirements or that the operation of the Software will be uninterrupted or error free. However Tait warrants that the diskettes if any on which the Software is supplied to the Licencee shall be free from defects in material and workmanship under normal use and service for a period of ninety (90) days from the date of delivery to the Licencee.

Exclusion of liability

Tait's entire liability and the Licencee's exclusive remedy shall be:

1. The replacement of any diskette not meeting Tait "limited warranty" and which is returned to Tait or an authorised agent or subsidiary of Tait with a copy of the Licencee's purchase receipt; or
2. If a diskette is supplied and if Tait is unable to deliver a replacement diskette that is free from defects in material or workmanship, the Licencee may terminate this Agreement by returning the Software to Tait.
3. In no circumstances shall Tait be under any liability to the Licencee, or any other person whatsoever, for any direct or consequential damage arising out of or in connection with any use or inability of using the Software.
4. Tait warrants the operation of the Software only with the operating system for which it was designed. Use of the Software with an operating system other than that for which it was designed may not be supported by Tait, unless otherwise expressly agreed by Tait.

General

The Licencee confirms that it shall comply with the provisions of law in relation to the Software.

Law and jurisdiction

This Agreement shall be subject to and construed in accordance with New Zealand law and disputes between the parties concerning the provisions hereof shall be determined by the New Zealand Courts of Law. Provided however Tait may at its election bring proceedings for breach of the terms hereof or for the enforcement of any judgement in relation to a breach of the terms hereof in any jurisdiction Tait considers fit for the purpose of ensuring compliance with the terms hereof or obtaining relief for breach of the terms hereof.

No dealings

The Licencee may not sublicense, assign or transfer the licence or the program except as expressly provided in this Agreement. Any attempt otherwise to sublicense, assign or transfer any of the rights, duties or obligations hereunder is void.

No other terms

The Licencee acknowledges that it has read this agreement, understand it and agree to be bound by its terms and conditions. The Licencee further agrees that this is the complete and exclusive statement of the agreement between it and Tait in relation to the Software which supersedes any proposal or prior agreement, oral or written and any other communications between the Licencee and Tait relating to the Software (LS-589).