

TB8100 Subrack Configurations

Base Station / Repeater / Link - AC and/or DC

<p>TBA2325-A000 <i>Single 5/50 W</i> Single channel subrack, 5 to 50 Watt Tx, AC and/or DC. Subrack can also be Receive-Only by fitting 1 x KOP XBAK2290.</p>	<p>TBA2326-A000 <i>Dual 5/50 W</i> Dual channel subrack, each channel 5 to 50 Watt Tx, AC and/or DC. Subrack can also be Receive-Only by fitting 2 x KOP XBAK2290.</p>	<p>TBA2327-A000 <i>Single 100 W</i> Single channel subrack, up to 100 Watt Tx, AC and/or DC.</p>	<p>TBA2328-A000 <i>Single 5/50W + Power Save</i> Single channel subrack, 5 to 50 Watt Tx, AC and/or DC, Power Save.</p>	<p>TBA2329-A000 <i>Single 100W + Power Save</i> Single channel subrack, up to 100 Watt Tx, AC and/or DC, Power Save.</p>
FRONT VIEWS	FRONT VIEWS	FRONT VIEWS	FRONT VIEWS	FRONT VIEWS
REAR VIEWS	REAR VIEWS	REAR VIEWS	REAR VIEWS	REAR VIEWS

Base Station / Repeater / Link - 12VDC

<p>TBA232A-A000 <i>Single 5/50W 12VPA</i> Single channel subrack, 5 to 50 Watt Tx, 12VDC input.</p>	<p>TBA232B-A000 <i>Dual 5/50W 12V PA</i> Dual channel subrack, each channel 5 to 50 Watt Tx, 12VDC input.</p>	<p>TBA232D-A000 <i>Single 5/50W 12VPA+Power Save</i> Single channel subrack, Power Save, 5 to 50 Watt Tx, 12VDC input.</p>	<p>TBA232E-A000 <i>Dual 5/50w 12VPA+Power Save</i> Dual channel subrack, Power Save, 5 to 50 Watt Tx, 12VDC input.</p>
FRONT VIEWS	FRONT VIEWS	FRONT VIEWS	FRONT VIEWS
REAR VIEWS	REAR VIEWS	REAR VIEWS	REAR VIEWS

Base Station / Repeater / Link - Dual Upgradable

<p>TBA232C-A000 <i>Single 5/50W Dual Upgradable</i> Easily upgradable to dual channel subrack, each channel 5 to 50 Watt Tx, AC and/or DC.</p>	<p>TBA232F-A000 <i>Single 5/50W 12VPA Dual Upgradable</i> Easily upgradable to dual channel subrack, each channel 5 to 50 Watt Tx, 12VDC input, Power Save.</p>
FRONT VIEWS	FRONT VIEWS
REAR VIEWS	REAR VIEWS

Base Station / Repeater - Dual Receivers

<p>TBA232G-A000 <i>Single 5/50W Dual Receiver</i> Single channel with Monitor Rx subrack, 5 to 50 Watt Tx, AC and/or DC.</p>	<p>TBA232H-A000 <i>Single 100W Dual Receiver</i> Single channel with Monitor Rx subrack, up to 100 Watt Tx, AC and/or DC.</p>
FRONT VIEWS	FRONT VIEWS
REAR VIEWS	REAR VIEWS

Receive-Only
Subracks TBA2325-A000 and TBA2326-A000 can be used for Receive-Only with PMU.

<p>TBA232K-A000 <i>Single Receive-Only</i> Reciter, no PMU</p>	<p>TBA232L-A000 <i>Dual Receive-Only</i> Two Reciters, no PMU</p>
FRONT VIEWS	FRONT VIEWS
REAR VIEWS	REAR VIEWS

Control Panels

<p>XBA2010 Power Save Control Panel</p>	<p>XBA2020 Standard Control Panel</p>	<p>XBA2040 Two Channel Control Panel</p>
--	--	---